STIC Phone: 3 PTO 2003-3840	SPE Signature Required for RUSH
S.T.I.C. Translations Branch Fill out a separate Request Form for each document. *U. S. Serial No.: 09/680280	SPE Signature Required for RUSH SPE 3663 SPE 3663
*Requester's Name: Dalena Tran	Phone No.: 308 8223
Office Location: PKS 3AS Art Unit/	Org. : _3(del
Date of Request: 6/5/03 *Date Needed By: 6/15/03 (Please indicate a specific date)	
Document Identification (Select One): Note: If submitting a request for <u>patent</u> translation, it is not necessary to attach a copy of If requesting a <u>non-patent</u> translation, please attach a complete, legible <u>copy</u> of the docum STIC Library.	
1. Y Patent *Document No. EP 082 *Country Code FR *Publication Date	Translations Branch The world of foreign prior art to y
*Language *Language No. of Pages (filled by STIC)	<u>-C/_</u> Translations
Article *Author *Language *Country	Equivalent Patents Searching
Other *Type of Document *Country *Language	
To assist us in providing the most cost effective ser	vice, please answer these questions:
 Will you accept an English Language Equivalent? Would you like to review this document with a translator. 	(Yes/No) prior to having a complete written translation?Yes/No) prior to having a complete written translation?(Yes/No) prior the default for Japanese Patents 1993 onwards with an
Date filled: Equivalent found: (Yes No) Doc. No.: Translate	Date logged in:
Search and Information Resources Administration	USPTO

WEST

Generate Collection Print

L16: Entry 1 of 2

File: EPAB

Mar 4, 1998

PUB-NO: EP000826946A1

DOCUMENT-IDENTIFIER: EP 826946 A1

TITLE: Method for assisting the piloting of an aircraft

PUBN-DATE: March 4, 1998

INVENTOR-INFORMATION:

NAME COUNTRY

DEKER, GUY FR
BOMANS, MURIEL FR

ASSIGNEE-INFORMATION:

NAME COUNTRY

SEXTANT AVIONIQUE FR

APPL-NO: EP97401989

APPL-DATE: August 26, 1997

PRIORITY-DATA: FR09610621A (August 30, 1996)

INT-CL (IPC): $\frac{G01}{G01} \frac{C}{C023/00}$ EUR-CL (EPC): $\frac{G01}{G01} \frac{C}{C023/00}$

ABSTRACT:

CHG DATE=19990617 STATUS=0> The method involves using a processor (2) and a terminal (4) with memories (3) for storage of flight information. The system is connected to other electronic equipment (9,14,15,16) which is mounted on board the aircraft. To determine a new flight plan in response to a new situation, the processor carries out an interpretation of the events as they occur, in order to determine the necessary corrective action. The processor takes account of the context in which the aircraft is found at the time and carries out analysis of possible reconfiguration of the flight plan. The processor determines the flight plan solutions which satisfy the new conditions and presents them on the terminal (4) in association with the significant parameters which have motivated the selection of the new plans.